

REGAL THEATRE SPECIFICATIONS

The standard house rig can be altered to your specifications at an additional cost. Additional lighting stock is available for hire at a reduced rate for theatre use.

| Quantity | Luminare |
|----------|--|
| 6 | 1kw 12/28 Zooms Pacific |
| 12 | ETC Source 4 26 deg Profiles |
| 12 | 650kw 18/34 Zooms Axial Acclaim |
| 8 | 2kw Fresnels Selecon: Arena |
| 16 | 1kw Fresnels Selecon: Rama |
| 4 | 650kw Fresnels |
| 40 | 1kw Par 64 MFL Single (110v) |
| 5 | 1.25kw Iris 4's |
| 6 | ETC Source 4 15/30 deg Profiles |
| 8 | ETC Source 4 25/50 Zoom Profiles |
| 204 | Channels of re-locatable 2.5K Jands HPX 12 AZ100 Dimmers |
| 1 | ETC CONGO JR Dual Video Console; 3072 Max Ch Output with Wireless Remote |
| 1 | ETC Universal Fader Wing 2 x 20 Channel |
| 3 | JANDS DD6-3 DMX 512 Distributors |
| | |

| | LX Control |
|-----|--|
| 1 | ETC CONGO JR Dual Video Console; 3072 Max Ch Output with Wireless Remote |
| 1 | ETC Universal Fader Wing 2 x 20 Channel |
| 3 | JANDS DD6-3 DMX 512 Distributors |
| 204 | Channels of re-locatable 2.5K Jands HPX 12 AZ100 Dimmers |